



20-23
ZERO TURN
MOWERS





### **CONTENTS**

Global Dealer Network	4 – 5
Work. Done Well	6 – 7
RIDING LAWN MOWERS	
X100 Series	10 – 13
Features	14–17
X300 Series	18
X500 Series	19
ZERO TURN MOWERS	
Z300 & Z500 Series	20 – 23
DIESEL MOWING TRACTORS	
X900 Series	24 – 25
LIFECYCLE SOLUTIONS	26 – 27
ATTACHMENTS	28 – 35
PRODUCT SPECIFICATIONS	26 /2
PRODUCI SPECIFICATIONS	36 – 43



JOHN DEERE is a member of EGMF – European Garden Machinery Federation

MEMBER OF



# NOTHING COMPARES TO OUR DEALERS

### **GLOBAL DEALER NETWORK**

At John Deere, we believe quality products and quality service go hand-in-hand. To ensure you always receive excellent advice and support, we only sell our lawn care products through authorised John Deere dealers.

Your local John Deere dealer is a fully-trained professional who knows our products inside out. From pre-sales advice to servicing and repairs, he's always there to ensure you enjoy your John Deere products to the max. John Deere dealers are all around the world and just around the corner. To find one near you, visit dealerlocator.deere.com

### WHICH MODEL?

Your John Deere dealer has the ideal machine for every task and can also show you how to use your new machine safely and appropriately. John Deere dealers regularly participate in training programmes and have years of experience.

### **USEFUL TIPS**

Your John Deere dealer prepares every machine you buy so it's ready to use when you get home. They also provide practical advice on how to achieve high economy and long years of service.



### **QUICK REPAIRS**

On the rare occasion when your John Deere machine needs repairs, your dealership service centre can fix it quickly.

### FRIENDLY SERVICE

The people at your local John Deere dealership are always there for you – with personal service you can rely on. As part of the John Deere community, they combine their own individual style with all the benefits of a strong global company.

### LONG-TERM SUPPORT

A John Deere machine is for life. Even after long years of service, we make sure you can still order any spare parts your model may need. Thanks to our close-knit dealer network, help is never far away.

### **ANY QUESTIONS?**

Our experienced dealer network is ready and waiting to assist you. Find a John Deere dealer in your area: dealerlocator.deere.com





Your local John Deere dealer is a fully-trained professional who knows our products inside out.



# WORK DONE WELL.

The main joy of being a homeowner is in creating something that is all your own. It's in sparking a vision and bringing it to life. But you know from experience that nothing great comes without hard work. A beautiful lawn and garden doesn't happen overnight.

That's why you take so much care in what you do. It's your attention to detail that makes all the difference. Your home is a place to be proud of and you deserve tools that feel the same way.

To do your best, you need top quality machines – machines that homeowners everywhere have been using for decades to turn their visions into reality. That's John Deere.











# X100 SERIES

### FLEXIBLE & DEPENDABLE

With six models and a wide range of features and options to choose from, the X100 Series has something for everyone. Designed for lawns of 3,000 to 6,000 m<sup>2</sup>, these robust lawn tractors are engineered for years of trouble-free service and combine superb cut quality with outstanding ease of use.



# UP TO YEARS\* PROTECTION

### **BUILT-IN PEACE OF MIND**

Your customer warranty covers unlimited hours for the first 2 years. Have your machine serviced annually by an authorised John Deere Dealer and your cover is extended to 3 years or 120 hours, whichever comes first.

\* For private residential use only. For commercial use of the X100 Series lawn mowers, the warranty is 12 months.

# CONTROLS ARE EASY TO FIND AND CONVENIENT TO USE

The contoured dash is functional and attractive, with controls logically placed and colour-coded for easy operation. A spring-assisted, low-effort lift lever simplifies setting and adjusting the mower cut height in 0.64-cm (0.25-inch) increments.


### **OIL CHANGES ARE MORE CONVENIENT**

The John Deere Easy Change™ 30-second oil change system makes complete oil changes a thing of the past. The canister holds 40 percent more oil, the engine runs cooler, and the entire process is easy, quick and clean. Smart design greatly reduces the risk of spillage, while the auto-closing oil filter valve prevents filtered particles from draining back into the engine when it stops. Standard on the X167.









### INTUITIVE TRANSMISSION CONTROL

With these Side-by-Side Pedals, you can control direction and speed without raising a foot. The automotive-type accelerator control ensures easy operation, while the large pedal surface provides superior comfort during use. The cruise control makes the ride easier. Standard on the X127 and X167.

### **CLEAR, MODERN FUEL GAUGE**

No need to get up: even on sunny days, the digital fuel gauge is clearly legible from the comfort of your seat (X127 and X167 only).





### TWO WAYS TO DISCHARGE

Sturdy, efficient mower decks come standard on the X107, X127 and X167 and have a wash port for quick, painless cleaning. Side discharge recycles grass clippings onto your lawn as a nutrient-rich natural fertiliser, while rear discharge captures clippings in a 300-litre collector – standard on the X117R, X147R and X167R.



### **COMFORT AND CONVENIENCE**

Our X100 Series lawn tractors are the cool solution for people who enjoy mowing and want a hassle-free machine that makes life easy. The ergonomic operator station has colour-coded controls for easy operation, plus an adjustable seat for a smoother ride. Control your speed and direction effortlessly with the Side-by-Side pedals – no need to lift a foot. You can even adjust cutting height on the fly just by sliding a lever!



## DISCOVER OUR WIDE RANGE OF ATTACHMENTS

Pages 28 – 35



### X107

Forward speed: 8.9 km/h (5.5 mph)

### **MOWER DECK**

42 Edge<sup>™</sup> (107 cm / 42 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 11.11 kW (14.9 hp)\* at 3,200 rpm
- Deck engagement: mechanical
- Seat: standard
- Mulch cover: optional
- Mulching kit: optional
- Collection system: optional
- Bumper: optional



### X127

Forward speed: 8.9 km/h (5.5 mph)

Cruise control

### **MOWER DECK**

42 Edge<sup>™</sup> (107 cm / 42 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 12.36 kW (16.9 hp)\* at 3,050 rpm
- Deck engagement: mechanical
- Seat: open back seat
- Mulch cover: standard
- Mulching kit: optional
- Collection system: optional
- Bumper: optional



### X167

Forward speed: 8.9 km/h (5.5 mph)

Cruise control

### **MOWER DECK**

48 Edge<sup>™</sup> (122 cm / 48 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 15.00 kW (20.1 hp)\* at 3,350 rpm
- Easy change 30-second oil change system
- Deck engagement: electric
- Seat: open back seat
- Mulch cover: standard
- Mulching blade: optional– Collection system: optional
- Bumper: standard



### **X117R**

Forward speed: 8.9 km/h (5.5 mph)

Rear collection

### **MOWER DECK**

36 Rear discharge (92 cm / 36 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 10.84 kW (14.5 hp)\* at 3,100 rpm
- Deck engagement: mechanical
- Collection capacity: 300 ltr
- Seat: standard
- Mulching kit: optional
- Bumper: optional



### X147R

Forward speed: 8.9 km/h (5.5 mph)

Rear collection

### **MOWER DECK**

36 Rear discharge (92 cm / 36 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 12.36 kW (16.9 hp)\* at 3,050 rpm
- Deck engagement: electric
- Collection capacity: 300 ltr
- Seat: standard high
- Mulching kit: optional
- Bumper: optional



### **X167R**

Forward speed: 8.9 km/h (5.5 mph)

Rear collection

### MOWER DECK

42 Rear discharge (107 cm / 42 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 12.36 kW (16.9 hp)\* at 3,050 rpm
- Deck engagement: electric
- Collection capacity: 300 ltr
- Seat: standard high
- Mulching kit: optional
- Bumper: standard

<sup>\*</sup> The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque could be less.

# **FEATURES**

### X300 & X500 SERIES

Access all areas: Designed for large lawns, these lawn tractors have all the power and comfort you need to get things done. The X300 Series models have impressive features and are easy to operate. For ultimate performance and power choose the X500 Series. Low centre of gravity, long wheelbase and differential lock make these machines the perfect all-round performers.

### **BUILT-IN PEACE OF MIND**

Your customer warranty covers unlimited hours for the first 2 years. Have your machine serviced annually by an authorised John Deere Dealer and your cover is extended to 4 years or 300 hours (X300) or 500 hours (X500), whichever comes first.

\* For private residential use only. For commercial use of X300 & X500 the warranty is 12 months with unlimited hours.









# TWIN TOUCH™ PEDALS MAKE MOWING SIMPLER

The highly efficient Twin Touch™ Hydrostatic Pedals allow you to easily control the speed and direction of travel without lifting your foot off the platform. The automotive-type accelerator control is familiar to use and the large pedal surface provides superior operator comfort.

### **GIVE YOUR FEET A REST**

Cruise control works at the push of a button, just like it does in your car, and comes standard on all X300, X500 and X900 Series lawn tractors.





### **ULTRA-COMFORTABLE SEATS**

Experience the ultimate in driving pleasure. Whatever the terrain, the Deluxe seat (standard on the X350 and X350R) and the Deluxe High seat (standard on the X370, X380 and the X500 Series) turns mowing into an enjoyable, comfortable pastime.



### **CLEAN & MODERN DISPLAY**

The clear, car-style instrument cluster is backlit for excellent visibility in all conditions, providing important feedback without distracting operators. The contoured dash is functional and attractive, with controls logically placed and colour-coded for convenient use. Separate engine speed and choke controls make warming up and starting the engine easier in cold weather.



### **ELECTRONIC FUEL GAUGE**

The clear, automotive-style gauge on the dash tells you at a glance how much fuel you have left. It's clearly visible in any conditions (not on X350R model which has low level indicator).



### **OPTIMUM "BEST CUT" TARGET ZONE**

The display shows you the optimum engine speed for outstanding cut quality. Always stay in the ultimate cut zone.



### 1 | 4-WHEEL STEERING

Standard on the X584 for outstanding manoeuvrability and easy trimming around obstacles.

### 2 | THE ACCEL DEEP™ MOWER DECKS

deliver new levels of cut quality, productivity, cleanliness, durability and versatility: 11.4 cm (4.5 in) deep throughout the entire deck shell for optimum mowing, mulching and bagging performance. The forged steel design eliminates sharp edges and corners where material can build up and diminish mowing performance.

### 3 | ADJUSTING CUTTING HEIGHT

Use the convenient dial to adjust the cutting height in  $6 \, \text{mm} \, (0.25 \, \text{in})$  steps – all from the comfort of your seat.

### 4 | SMOOTH-RUNNING V-TWIN ENGINE

The V-twin engine has electronic fuel injection (EFI) and a constant-speed governor for quick starts and superior mowing performance (X590 only).







# X300 SERIES

### ON ALL **X300 SERIES** MODELS

- Deck engagement: electric
  Twin Touch™ foot pedals
- Cruise control
- Digital display panel



### X350

Forward speed: 8.9 km/h (6.4 mph)

### **MOWER DECK OPTIONS**

42 Edge™ mulch (107 cm / 42 in)

42 Accel Deep<sup>™</sup> (107 cm / 42 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 13.7 kW (18.4 hp)\* at 3,200 rpm
- MulchControl™: Standard with 42 Accel Deep™
- Collection system: optional (42 Accel Deep<sup>™</sup>)
- Seat: Deluxe (38 cm / 15 in)



### **X350R**

Forward speed: 8.9 km/h (6.4 mph)

Rear collection

### **MOWER DECK**

42 Rear Discharge (107 cm / 42 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 13.7 kW (18.4 hp)\* at 3,200 rpm
- Mulch Plug: standard
- Seat: Deluxe (38 cm / 15 in)



### X370

Forward speed: 8.9 km/h (6.4 mph)

Hydraulic, 2-wheel power steering

### **MOWER DECK OPTIONS**

42 Edge<sup>™</sup> mulch (107 cm / 42 in)

42 Accel Deep™ (107 cm / 42 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 13.7 kW (18.4 hp)\* at 3,200 rpm
- Deck lift system: hydraulic
- MulchControl™: Standard with 42 Accel Deep™
- Collection system: optional (42 Accel Deep<sup>™</sup>)
- Seat: Deluxe High (46 cm / 18 in)



### X380

Forward speed: 10.0 km/h (5.6 mph)

### **MOWER DECK OPTIONS**

48 Accel Deep<sup>™</sup> (122 cm / 48 in)

54 Accel Deep<sup>™</sup> (137 cm / 54 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 14.7 kW (19.7 hp)\* at 3,200 rpm
- MulchControl<sup>™</sup>: optional
- Collection system: optional
- Seat: Deluxe High (46 cm / 18 in)

### **DISCOVER OUR WIDE RANGE OF ATTACHMENTS**

Pages 28 – 35

# X500 SERIES

### ON ALL **X500 SERIES** MODELS

- Deck engagement: electric
- Cruise control
- Deluxe high seat
- Power Steering
- Twin Touch™ foot pedals
- Digital display panel



### X584

Forward speed: 11.6 km/h (7.2 mph)

Hydraulic, 4-wheel power steering

### **MOWER DECK OPTIONS**

48 Accel Deep™ (122 cm / 48 in)

54 Accel Deep™ (137 cm / 54 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 16.1 kW (21.9 hp)\* at 3,350 rpm
- Deck lift system: hydraulicMulchControl™: optional
- Collection System: optional
- Seat: Deluxe Extra High (53 cm / 21 in)



### X590

Forward speed: 11.6 km/h (7.2 mph)

Hydraulic, 2-wheel power steering

### **MOWER DECK OPTIONS**

48 Accel Deep<sup>™</sup> (122 cm / 48 in)

54 Accel Deep<sup>™</sup> (137 cm / 54 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 16.7 kW (22.7 hp)\* at 3,250 rpm
- Deck lift system: hydraulic
  MulchControl™: optional
- Collection System: optional
- Seat: Deluxe Extra High (53 cm / 21 in)







### **MULCHING JUST GOT EVEN EASIER**

Meet MulchControl™ – the perfect option for great mulching performance and versatility. This easy to use system lets you switch from side discharge to mulching (and back again) simply by flipping a lever. MulchControl™ works together with our special mulching blades and is available as an option on all X300 and X500 Series ride on tractors (excluding X350R).

To use the Power Flow™ rear bagger with the MulchControl™ attachment and mulching blades installed, just set the lever to the "side discharge" position.

# ZTRAK™ ZERO-TURN MOWERS

### QUICKER ALL-ROUND

With their outstanding agility and speeds of up to 14.5 km/h, our ZTrak™ zero-turn mowers help you get a great finish faster. There are two series with six models in total to choose from, including one that's just right for your garden.

### **BUILT-IN PEACE OF MIND**

Your customer warranty covers unlimited hours for the first 2 years. Have your machine serviced annually by an authorised John Deere Dealer and your cover is extended to 3 years or 120 hours, whichever comes first.

\* For private residential use only. For commercial use of the Z300 Series lawn mowers, the warranty is 12 months.







### 360° AGILE

When it comes to manoeuvrability, the ZTrak™ runs rings round other mowers – even ours! Combine that with exceptional trimming performance and it's easy to see why so many professionals turn to ZTrak™.

# COMFORT AND CONVENIENCE IN EVERY DETAIL

### 1 | COMFORTGLIDE™

Available for the Z530M and Z545R, the seat cushions shock by gliding forwards and backwards as much as 5.1 cm (2 in) during sudden starts and stops or in rough terrain.

### 2 | PARK BRAKE

Very convenient: As soon as you put the motion-control levers of the Z300 Series into the parking position, the parking brake is engaged automatically.

### **3 | TURN ON THE SPOT**

The motion-control levers can be adjusted to two different height settings and eighteen different fore-aft settings, enhancing operator comfort and providing more precise control.











### **MOW FAST, MOW WELL**

To adjust the height of cut from the comfort of your seat, simply turn the dial (Z300 Series) or move the pin between 25 – 104 mm (1 – 4 in) in 6 mm (0.25 in) increments (Z500 Series). Together with our Accel Deep $^{\rm m}$  or High Capacity decks, this system ensures outstanding cut quality with a minimum of fuss.

# **Z300 & Z500 SERIES**

### **3 LEVELS OF COMFORT**

### ON ALL ZTRAK™ ZERO-TURN MOWERS

- 25 102 mm (1 4 in) cutting height, increments 6 mm (0.25 in)
- Deck engagement: electric
- Collection system: optional

Our E-Series come with everything you need for a smooth, consistent cut. M-Series models add more comfort such as a higher seat, while R-Series model offer the ultimate in comfort and convenience.

### 1 | COLLECTION CAPACITY

Easily convert your  $\mathsf{ZTrak}^\mathsf{m}$  mower into a collection machine by adding an optional collection system.

### 2 | Z545R WIT ELECTRONIC FUEL INJECTION ENGINE

The Z545R combines electronic fuel injection (EFI) and electronic throttle control (ETC) for outstanding fuel economy, power curve and ease of use. In lighter load conditions, press the eco-mode button to reduce engine rpm, noise and fuel bills further still.

### 3 | FOOT DECK LIFT

To raise, lower or change the mower deck height while you're working, simply press the foot bar.







 $<sup>\</sup>star$  The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque could be less.

## DISCOVER OUR WIDE RANGE OF ATTACHMENTS

Pages 28 – 35



### **Z315E**

Forward speed: 11.3 km/h (7 mph)

Seat back height: 45.7 cm (18 in)

Speed and direction: Twin levers

### **MOWER DECK**

42 Accel Deep™ (107 cm / 42 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 12.1 kW (16.2 hp)\* at 3,000 rpm
- Mulching: optional (MulchControl™)



### **Z320M**

Forward speed: 11.3 km/h (7 mph)

Seat back height: 50.8 cm (20 in)

Armrests (optional)

Speed and direction: Twin levers

### **MOWER DECK**

42 Accel Deep™ (107 cm / 42 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 12.7 kW (17 hp)\* at 3,000 rpm
- Hitch
- Mulching: optional (MulchControl™)



### **Z320R**

Forward speed: 11.3 km/h (7 mph)

Seat back height: 50.8 cm (20 in)

Armrests

Speed and direction: Twin levers

### **MOWER DECK**

42 Accel Deep™ (107 cm / 42 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 12.7 kW (17 hp)\* at 3,000 rpm
- Hitch
- LED lights
- Floor Mats
- Covered Tool Storage
- Mulching: optional (MulchControl™)



### **Z515E**

Forward speed:  $12.9 \, \text{km/h} (8 \, \text{mph})$ 

Seat back height: 45.7 cm (18 in) medium-back

Armrests

Speed and direction: Twin levers

### **MOWER DECK**

48 Accel Deep™ (122 cm / 48 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 13.4 kW (18.0 hp)\* at 3,350 rpm
- Mulching: optional (MulchControl™)



### **Z530M**

Forward speed: 12.9 km/h (8 mph)

Seat back height: 50.8 cm (20 in)

Armrests

Speed and direction: Twin levers

### **MOWER DECK**

48 Accel Deep™ (122 cm / 48 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 16.1 kW (21.6 hp)\* at 3,350 rpm
- Floor mat
- Mulching: optional (MulchControl™)



### **Z545R**

Forward speed: 14.5 km/h (9 mph)

Seat back height: 57.1 cm (22.5 in)

Armrests

Speed and direction: Twin premium

### **MOWER DECK**

48 High Capacity (122 cm / 48 in)

- CE-Nominal Power (tested in accordance to SAE J1349): 15.3 kW (20.5 hp)\* at 3,250 rpm
- Floor mat and foot pegs
- LED lights
- Mulching: optional (Mulch Kit)

# X900 SERIES

### **DIESEL MOWING TRACTORS**

For the ultimate in professional performance, consider our legendary X900 diesel mowing tractors. They come in 2-Wheel Drive, 4-Wheel Drive / 4-Wheel Steer versions – plus a X950R rear discharge, rear collect model for uncompromising power and capacity.



Ask your dealer for the "Commercial Mowing Equipment" brochure today – or download it from JohnDeere.com

### MULCHCONTROL™

The MulchControl™ feature boosts productivity by reducing collection volumes (and emptying cycles) significantly when bagging. It also increases flexibility: if conditions are too poor to mulch properly, operators can convert to side discharge in just 30 seconds.

### **EASY TO USE HYDRAULICS**

Ergonomic levers hydraulically raise and lower the mower deck and attachments. A "float" position enables front-mounted equipment to follow ground contours. The intuitive countrols enable easy operation.





## **X940 SERIES MODELS**

- Engine, Nominal Power: 18 kW (24.5 hp)\* at 3,400 rpm – Twin Touch™ Foot Pedals
- Cruise Control
- Deck Lift System: Hydraulic
- Deck Engagement: Électric
- Road Homologation Kit: optional

# COMMERCIAL MOWER DECK OPTIONS

48 in Side Discharge (122 cm / 48 in)

54 in Side Discharge (137 cm / 54 in)

60 in Side Discharge (152 cm / 60 in)

– Cutting Height 25 – 133 mm (1 – 5.25 in), increments 6 mm (0.25 in)



### X940

Forward speed: 13.7 km/h (8.5 mph)

Hydraulic, 2 front wheel power steer

2-Wheel Drive

Optional standard or air suspension seat

- Collection System: 3-bag-bagger optional



### X948

Forward speed: 13.7 km/h (8.5 mph)

Hydraulic, 2 front wheel power steer

4-Wheel Drive

Optional standard or air suspension seat

- Collection System: 3-bag-bagger optional



### X949

Forward speed: 13.7 km/h (8.5 mph)

Hydraulic, 4 wheel power steer

4-Wheel Drive / 4-Wheel Steer

Optional standard or air suspension seat

- Collection System: 3-bag-bagger optional



### **X950R**

Forward speed: 14.5 km/h (9 mph)

Cruise Control

Hydraulic, 2 front wheel power steering

Collection System options: Low Dump / High Dump

Optional standard or air suspension seat

### COMMERCIAL REAR DISCHARGE **MOWER DECK OPTIONS**

122 cm / 48 in

137 cm / 54 in

- Engine, Nominal Power: 18.5 kW (25.2 hp)\* at 3,200 rpm
- Twin Touch™ Foot Pedals
- Deck Lift System: Hydraulic
- Deck Engagement: Electric
- Road Homologation Kit: optional



<sup>\*</sup>The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque could be less.

# **LIFECYCLE SOLUTIONS**

### TOTAL LIFETIME CARE

Our comprehensive suite of industry-leading support services is focused on keeping your riding lawn equipment performing as well as on the day it left the factory.

No matter what happens, when it happens, or how old or new your machine is – we've created forward-thinking solutions that make sure nothing stands in the way of your productivity.





# PREMIUM COMPONENTS AND SCHEDULED ROUTINE MAINTENANCE.

Your machine is built to last. That makes it easy for you to keep it in great shape by giving it some basic preventive care. Start by using only original premium components designed for your machine, regularly perform scheduled routine maintenance, and prepare your machine with winter inspections carried out by skilled technicians.



# FIXING ISSUES AS QUICKLY AS POSSIBLE.

Even in challenging situations, you are in the best hands thanks to excellent parts availability from dealer stock, our superior parts logistics infrastructure, and skilled dealer technicians who work only with the latest factory-approved tools and diagnostics.



### **↑** UPGRADE

# INSTALLING PERFORMANCE & COMFORT UPGRADES.

Upgrade to higher levels of performance and comfort and discover how you can accomplish more in less time by upgrading to enhanced comfort features, boosting machine performance, and adding attachments to extend machine versatility.






Scan the QR code to quickly find and buy the right attachments for your lawn tractor.













# **MOWING**

In the end, it's all about the cut. Our precision-engineered mower decks make sure your lawn always has a clean, even cut and a manicured appearance. As for the clippings, the choice is yours: mulch, collect or side discharge.

### 1+2 | OPTIONAL MULCHCONTROL™

Switch from side discharge to mulching (or vice-versa) just by flipping a lever.

For the X940 Series, MulchControl™ can also be operated using an hydraulic lever from the seat (optional).

See page 24 for details.

### 3 | MULCH KIT

X100 Series

Effortlessly convert the mower decks of the X100 Series to the mulching function. Includes a set of mulching blades and a mulching cover for the mower deck housing.

# **WEIGHTS**

3

### 4 | WHEEL AND SUITCASE

X100, X300, X500, X900 Series

Front weighting is recommended for rear grass collectors on slopes and may also be required with heavy rear-mounted equipment. Rear weights are recommended for additional traction, especially when using snow blades, brooms and snow blowers.

# **SPREADER**

### 5 | TOW-BEHIND SPREADER, 80 KG

X100, X300, X500, X900 Series

This poly hopper has a capacity of 100 litres or 80 kg. Features include Autoflow, which stops material from spreading when the tractor stops, and Directional Flow Control, which adjusts the spread pattern away from paths, driveways and flowerbeds. The hopper has a long steel handle for quick, easy opening/closing and stainless steel hardware to prevent internal rust and corrosion. The enclosed gearbox is maintenance-free, and the tubeless pneumatic tyres keep rolling resistance low.

### **6 | REAR DEFLECTOR**

X117R, X147R, X167R, X350R, X950R

Deflects clippings in an even pattern behind the tractor. Easily installed in place of a hopper; no tools required.



# **COLLECTION**

Our grass collectors are the ideal way to efficiently collect grass clippings and leaves. The hopper design ensures great collection performance and cleaner operation, making it easy to empty the bags.

The Power Flow™ System has a hinged blower for easy installation. The blower fan rotates clockwise (seen from the right) to move material up to the chute efficiently. The lightweight polyethylene blower fan and housing keep the material flowing smoothly, together with the large diameter chute. When the bags are almost full, the fill indicator helps prevent chute blocking, alerting you in good time.

### 1+2 | 230 LTR COLLECTION SYSTEM

ge™ Deck and Ige™ Deck
cel Deep™ Deck nal in combination Mulchcontrol™
cel Deep™ Deck, r Flow™ Collection System
gh Capacity Deck, r Flow™ Collection System









# **MATERIAL COLLECTION SYSTEM**

### 3 | 500 LTR POWER FLOW™ COLLECTION SYSTEM

X584, X590	48 Accel Deep™ Deck 54 Accel Deep™ Deck
X940 Series	48 Accel Deep™ Deck 54 HC 60 HC

### **250 LTR COLLECTION SYSTEM**

X350, X370	42 Accel Deep <sup>™</sup> Deck
X940 Series	48 Accel Deep™ Deck 54 HC 60 HC

### 4 | 250 LTR POWER FLOW™ COLLECTION SYSTEM

X380	48 Accel Deep™ Deck 54 Accel Deep™ Deck
X584, X590	48 Accel Deep™ Deck 54 Accel Deep™ Deck

# **SNOW REMOVAL**









### 1+2 | FRONT BLADE

X100 Series	117cm (46 in) Front blade
X300 Series	112 cm (44 in) Front blade
X500 Series	122 cm (48 in) Front blade
X900 Series	137 cm (54 in) Front blade

These front blades are excellent for moving snow or other loose material forward, to the right or left. The curved blade surface is designed to roll material, not push it, which requires less power and increases blade capacity.

### 3 | TYRE CHAINS (PAIR)

X100, X300, X500, X900 Series

Recommended for use with front blade or snow blowers.

### 4 | SNOW BLOWER

X900 Series 120 cm (47 in) quick-hitch

Snow blowers offer a high quality product with full height housings which are forged from heavy gauge steel, which, together with their heavy duty, two-stage design, provide superior performance and long life. A quick-hitch mounting system helps take the effort out of installation and removal of the snow blowers. The snow blower fits and locks onto the front hitch with attached snap pins.

# **TOOLS / MOUNTINGS**







### 1 | STRING TRIMMER MOUNT

Z515E, Z530M, Z545R

The main bracket fits snugly over the right-side fender, and the secondary bracket mounts to the caster arm, securely held in place with rubber straps. Not compatible with a complete material collection system.

### 2 | TOOLBOX

Z515E, Z530M, Z545R

The John Deere ZTrak™ toolbox gives you easy access and convenient storage for small, handheld tools and securely mounts to the front of the frame.

### **YARD TOOL KIT**

Z515E, Z530M, Z545R

Take yard tools like rakes and shovels with you on the machine. You can mount the brackets of the yard tool kit on either side of the rear engine shroud to carry a maximum of two yard tool kits.

### 3 | FRONT JACK KIT

Z515E, Z530M, Z545R

Get easy access to the underside of the mower for maintenance or blade changes while in the field. The kit contains everything you need to install the jack onto the front of your mower.

# **TRANSPORT**

Available with a steel or poly bed, these tow carts are ideal for hauling lawn debris, sand, dirt, mulch or plants. They are designed for easy dump release and tilt at a steep angle for complete emptying of material. The steel cart has a bracketless tailgate, so there are no side channels to obstruct materials when emptying. The recessed bolt heads never get in the way during shovelling. The heavy duty poly bed is rust and dent resistant and extremely durable. It is available in two sizes.









### 1 | UTILITY CART, POLY

X100, X300, X500, X900 Series	7P	160 ltr
X100, X300, X500, X900 Series	10P	240 ltr

### 2 | UTILITY CART, STEEL

X100, X300, X500 X900 Series	Cart 13	280 ltr
X500, X900 Series	Cart 18	420 ltr

### 3 | EASY CHANGE OIL FILTER SYSTEM

X167

A very convenient way to make oil changes: easy, clean, and in only 30 seconds.

### 4 | HOME MAINTENANCE KIT

X100, X300, X500 Series

The easiest way to order all the maintenance parts specified in the operator's manual. Kit includes engine oil filter, engine oil, fuel filter, fuel filter element and air filter element foam, as well as spark plug(s) for petrol engines.


# PROTECTION / REAR RECEIVER / HITCH KIT













### 1 | FRONT BUMPER

X100 Series	Double Bar
X300 Series	Single Bar

Give your tractor a sharper, more assertive look while protecting its front from damage.

### 2 | QUICK-TATCH WEIGHT 19 KG

X100, X300, X500 Series

These cast iron weights let you counter-balance a heavy attachment and/or provide greater traction and stability. Weight bracket required in some applications.

### 3 | REAR BUMPER

Z315E, Z320M, Z320R rear bumper comes with rear hitch in a kit, Z515E, Z530M, Z545R

Bolts to the tubular frame to protect the rear of your  $\mathsf{ZTrak}^\mathsf{m}$  mower.

### 4 | REAR TOWING HITCH

Z315E, Z320M, Z320R rear bumper comes with rear hitch in a kit, Z515E, Z530M, Z545R

Bolts solidly to the tubular frame. The rear bagger bracket is included with the rear hitch.

### 5 | BRUSH GUARD

X300 Series, X500 Series

Made of sturdy tubular steel for years of use, the brush guard provides a distinctive appearance and protects the front of the tractor.

### 6 | FOOT PEG AND RUBBER FLOOR MAT

Z300 Series, Z500 Series (Standard on Z345R, Z545R)

Makes mowing more comfortable.



# **SPECIFICATIONS**

### JOHN DEERE RIDING LAWN EQUIPMENT

Do you want to know everything and are ready to dive deep into the technical details? Here are our technical specifications laid out for easy comparison between all models.



### X100 SERIES

	X107	X127	X167	X117R	X147R	X167R
ENGINE						
Туре	Petrol	Petrol	Petrol	Petrol	Petrol	Petrol
CE Nominal Power and Speed in kW (hp)*	11.11 (14.9) at 3,200 rpm	12.36 (16.9) at 3,050 rpm	15.00 (20.1) at 3,350 rpm	10.84 (14.5) at 3,100 rpm	12.36 (16.9) at 3,050 rpm	12.36 (16.9) at 3,050 rpm
Displacement, cm³ (cu in)	500	656	724	500	656	656
Cylinder	Single, OHV	V-Twin, OHV	V-twin, OHV	Single, OHV	V-twin, OHV	V-twin, OHV
Fuel Capacity, Itr	9.1	9.1	9.1	7.5	7.5	7.5
TRANSMISSION						
Туре	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Drive system	Side-by-side Foot Pedals, 2-Wheel Drive	Side-by-side Foot Pedals, 2-Wheel Drive	Side-by-side Foot Pedals, 2-Wheel Drive	Side-by-side Foot Pedals, 2-Wheel Drive	Side-by-side Foot Pedals, 2-Wheel Drive	Side-by-side Foot Pedals, 2-Wheel Drive
Cruise Control	No	Yes	Yes	No	No	No
Forward/Reverse, km/h	8.9 / 4.8	8.9 / 4.8	8.9 / 4.8	8.9 / 3.2	8.9 / 3.2	8.9 / 3.2
STEERING						
Туре	2-Wheel Steer	2-Wheel Steer	2-Wheel Steer	2-Wheel Steer	2-Wheel Steer	2-Wheel Steer
Uncut Circle Radius, cm	63.5	63.5	50.8	68.6	68.6	71.1
MOWER DECK OPTIONS						
36 Rear Discharge (92 cm / 36 in)				-		
42 Edge™ Mulch (107 cm / 42 in)						
42 Edge™ (107 cm / 42 in)						
42 Accel Deep™ (107 cm / 42 in)						
42 Rear Discharge (107 cm / 42 in)						-
48 Edge™ (122 cm / 48 in)						
48 Accel Deep™ (122 cm / 48 in)						
54 Accel Deep™ (137 cm / 54 in)						
Mulching	Mulch Cover Optional, Mulch Kit Optional	Mulch Cover Standard, Mulch Kit Optional	Mulch Cover Standard, Mulch Kit Optional	Optional	Optional	Optional
Cutting Height, mm	25-100	25 – 101	25 – 101	25 – 90	25 – 90	25 – 100
Mower Deck Lift System	Manual	Manual	Manual	Manual	Manual	Manual
Mower Deck Engagement	Mechanical	Mechanical	Electric	Mechanical	Electric	Electric
COLLECTOR						
Standard/Optional	Optional	Optional	Optional	Standard	Standard	Standard
Capacity, Itr	230	230	230	300	300	300
SEAT TYPE	Standard	Open back seat	Open back seat	Standard	Standard High	Standard High
TYRES						
Size of Front	15 × 6 – 6	15 × 6 – 6	16 × 6.5 – 8	15 × 6 – 6	15 × 6 – 6	15 × 6 – 6
Size of Rear	20 × 8 – 8	20 × 8 – 8	22 × 9.5 – 12	18 × 18.5 – 8	18 × 8.5 – 8	18 × 8.5 – 8
DIMENSIONS						
Height (inc. Seat), cm (in)	102 (40)	112 (44)	114 (45)	102 (40)	102 (40)	102 (40)
Length, Overall, cm (in)	177 (70)	177 (70)	192 (76)	242 (95)	242 (95)	253 (100)
Width, cm (in)	118 (46)	118 (46)	131 (52)	96 (38)	96 (38)	111 (44)
Weight, approx., kg (lb)	193 (425)	205 (452)	228 (503)	234 (516)	239 (527)	246 (542)

<sup>■</sup> Standard □ Optional



 $<sup>{\</sup>color{red}^{\star}} \ The\ engine\ horsepower\ and\ torque\ information\ are\ provided\ by\ the\ engine\ manufacturer\ to\ be\ used\ for\ comparison\ purposes\ only.\ Actual\ operating\ horsepower\ and\ torque\ could\ be\ less.$ 

### X300 SERIES

	X350	X350R	X370	X380
ENGINE				
Туре	Petrol	Petrol	Petrol	Petrol
CE Nominal Power and Speed in kW (hp)*	13.7 (18.4) at 3,200 rpm	13.7 (18.4) at 3,200 rpm	13.7 (18.4) at 3,200 rpm	14.7 (19.7) at 3,200 rpm
Displacement, cm³ (cu in)	726	726	726	726
Cylinder	V-twin, OHV	V-twin, OHV	V-twin, OHV	V-twin, OHV
Fuel Capacity, Itr	11	7.9	11	11
TRANSMISSION				
Туре	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Drive system	Twin Touch™ Foot Pedals, 2-Wheel Drive	Twin Touch™ Foot Pedals, 2-Wheel Drive	Twin Touch™ Foot Pedals, 2-Wheel Drive	Twin Touch™ Foot Pedals 2-Wheel Drive
Cruise Control	Yes	Yes	Yes	Yes
Forward/Reverse.km/h	8.9 / 6.4	8.5 / 6.4	8.9 / 6.4	10.0 / 5.6
STEERING				
	2.111 15	2.141 15	Hydraulic Power	2.44 15
Туре	2-Wheel Steer	2-Wheel Steer	2-Wheel Steer	2-Wheel Steer
Uncut Circle Radius, cm	66 (42 Acel Deep™)	58.4 right side / 77.1 left side	76 (42 Accel Deep™)	53.3 (48 Accel Deep™)
MOWER DECK OPTIONS				
36 Rear Discharge (92 cm / 36 in)				
42 Edge™ Mulch (107 cm / 42 in)				
42 Edge™ (107 cm / 42 in)				
42 Accel Deep™ (107 cm / 42 in)				
42 Rear Discharge (107 cm / 42 in)				
48 Edge™ (122 cm / 48 in)				
48 Accel Deep™ (122 cm / 48 in)				
54 Accel Deep™ (137 cm / 54 in)				
Mulching	Standard with 42 Accel Deep™	Standard (mulch plug only)	Standard with 42 Accel Deep™	Optional
Cutting Height, mm	25-102	25 – 102	25-102	25-102
Mower Deck Lift System	Foot Pedal	Foot Pedal	Hydraulic	Foot Pedal
Mower Deck Engagement	Electric	Electric	Electric	Electric
COLLECTOR				
Standard/Optional	Optional only with 42 Accel Deep™ Deck	Standard	Optional only with 42 Accel Deep™ Deck	Optional only with 48 Accel Deep™ Deck, 54 Accel Deep™ Deck
Capacity, ltr	250	270	250	250
SEAT TYPE	Deluxe	Deluxe	Deluxe High	Deluxe High
TYRES				
Size of Front	15 × 6 – 6	15 × 6 – 6	15 × 6 – 6	15 × 6.5 – 8
Size of Rear	20 × 10 – 8	20 × 10 – 8	20 × 10 – 8	22 × 11 – 10
DIMENSIONS				
Height (inc. Seat), cm (in)	117.1 (46.1)	117.1 (46.1)	124.4 (49)	124.4 (49)
Length, Overall, cm (in)	181.7 (71.5)	246.8 (97.2)	181.7 (71.5)	183.6 (72.3)
Width, cm (in)	118 (46) (42 Edge™ Mulch)	111.3 (43.8)	118 (46) (42 Accel Deep™)	156 (61) (48 Accel Deep™)
Weight, approx., kg (lb)	255 (562) (42 Edge™ Mulch)	306 (674)	269 (594) (42 Accel Deep™)	301 (663) (48 Accel Deep

<sup>■</sup> Standard □ Optional



<sup>\*</sup> The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque could be less.

### **X500 SERIES**

	X584	X590
ENGINE		
Туре	Petrol	Petrol
CE Nominal Power and Speed in kW (hp)*	16.1 (21.9) at 3,350 rpm	16.7 (22.7) at 3,250 rpm
Displacement, cm³	726	726
Cylinder	V-Twin	V-Twin
Fuel Capacity, Itr	16.7	16.7
TRANSMISSION		
Туре	Hydrostatic	Hydrostatic
Drive System	Twin Touch™ Foot Pedals, 2-Wheel Drive	Twin Touch™ Foot Pedals, 2-Wheel Drive
Cruise Control	Yes	Yes
Forward / Reverse, km/h (mph)	11.6 / 8.4	11.6 / 8.4
STEERING		
Туре	Hydraulic Power 4-Wheel Steer	2-Wheel Steer
Uncut Circle Radius, cm	38.1 (48 Accel Deep™)	68.6 (48 Accel Deep™)
MOWER DECK OPTIONS		
42 Accel Deep™ (107 cm / 42 in)		
48 Accel Deep™ (122 cm / 48 in)		
48 High Capacity (122 cm / 48 in)		
54 Accel Deep™ (137 cm / 54 in)		
Mulching	Optional	Optional
Cutting Height, mm	25 – 102	25 – 102
Mower Deck Lift System	Hydraulic	Hydraulic
Mower Deck Engagement	Electric	Electric
COLLECTOR		
Standard / Optional	Optional	Optional
Capacity, ltr	250 or 500	250 or 500
SEAT TYPE	Deluxe High	Deluxe High
Seat back height	53 cm	53 cm
Armrest	Optional	Optional
TYRES		
Front Casters	16 × 6.5 – 8	16 × 6.5 – 8
Reartires	24 × 9.5 – 12	24 × 12 – 12
DIMENSIONS		
Height (inc. Seat), cm (in)	140 (55)	140 (55)
Length, Overall, cm (in)	191 (75)	201 (79)
Width, cm (in) – incl. Mower Deck	156 (61) (48 Accel Deep™)	156 (61) (48 Accel Deep™)
Weight, approx., kg (lb)	396 (873)	381 (840)
Standard   Ontional		

<sup>■</sup> Standard □ Optional



 $<sup>{}^{\</sup>star} \text{The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque could be less.}$ 



### **Z300 SERIES**

	Z315E	Z320M	Z320R
ENGINE			
Туре	Petrol	Petrol	Petrol
CE Nominal Power and Speed in kW (hp)*	12.1 (16.2) at 3,000 rpm	12.7 (17.0) at 3,000 rpm	12.7 (17.0) at 3,000 rpm
Displacement, cm <sup>3</sup>	656	726	726
Cylinder	V-Twin	V-Twin	V-Twin
Fuel Capacity, Itr	11.36	11.36	11.36
TRANSMISSION			
Туре	Hydrostatic	Hydrostatic	Hydrostatic
Drive System	Twin Stick Speed & Direction Control Levers, 2-Wheel Drive	Twin Stick Speed & Direction Control Levers, 2-Wheel Drive	Twin Stick Speed & Direction Control Levers, 2-Wheel Drive
Cruise Control	No	No No	
Forward / Reverse, km/h (mph)	11.3 / 7	11.3 / 7	11.3 / 7
STEERING			
Туре	Zero-Turn	Zero-Turn	Zero-Turn
Uncut Circle Radius, cm	Zero-Turn Radius	Zero-Turn Radius	Zero-Turn Radius
MOWER DECK OPTIONS			
42 Accel Deep™ (107 cm / 42 in)			
48 Accel Deep™ (122 cm / 48 in)			
48 High Capacity (122 cm / 48 in)			
Mulching	Optional (MulchControl™)	Optional (MulchControl™)	Optional (MulchControl™)
Cutting Height, mm (in)	31.75 – 114.3 (1.25 – 4.5), 14 increments ea. 6 mm (0.25)	31.75 – 114.3 (1.25 – 4.5), 14 increments ea. 6 mm (0.25)	31.75 – 114.3 (1.25 – 4.5), 14 increments ea. 6 mm (0.25)
Mower Deck Lift System	Manual – foot lift	Manual – foot lift	Manual – foot lift
Mower Deck Engagement	Electric	Electric	Electric
COLLECTOR			
Standard / Optional	Optional	Optional	Optional
Capacity, Itr	230	230	230
SEAT TYPE	Medium Back	High Back	High Back
Seat back height, cm (in)	45.7 (18)	50.8 cm (20 in)	50.8 cm (20 in)
Armrest	Optional	Optional	Standard
TYRES			
Front Casters	11 × 6.0	11 × 6.0	11 × 6.0
Rear tyres	18 × 8.5 – 8	18 × 8.5 – 8	22 X 10.00 – 8
DIMENSIONS			
Height (inc. Seat), cm (in)	105.6 (41.6)	110 (43.3)	112.3 (44.2)
Length, Overall, cm (in)	191.5 (75.4)	125.5 (77.8)	125.5 (77.8)
Width, cm (in) – incl. Mower Deck	128 (50.4)	128 (50.4)	128 (50.4)
Weight, approx., kg (lb)	252 (554)	255 (561)	278 (611)

<sup>■</sup> Standard □ Optional

 $<sup>\</sup>star$  The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque could be less.

### **Z500 SERIES**

	Z515E	Z530M	Z545R
ENGINE			
Туре	Petrol	Petrol	Petrol
CE Nominal Power and Speed in kW (hp)*	13.4 (18.0) at 3,350 rpm	16.1 (21.6) at 3,350 rpm	15.3 (20.5) at 3,250 rpm
Displacement, cm³	708 (43.2)	726 (44.3)	724 (44.2)
Cylinder	V-Twin	V-Twin	V-Twin
Fuel Capacity, Itr	17	17	17
TRANSMISSION			
Туре	Hydrostatic	Hydrostatic	Hydrostatic
Drive System	Twin Stick Speed & Direction Control Levers, 2-Wheel Drive	Twin Stick Speed & Direction Control Levers, 2-Wheel Drive	Twin Stick Speed & Direction Control premium Levers, 2-Wheel Drive
Cruise Control	No	No	No
Forward / Reverse, km/h (mph)	12.9 (8.0) / 6.4 (4)	12.9 (8.0) / 6.4 (4)	14.5 (9.0) / 7.2 (4.5)
STEERING			
Туре	Zero-Turn	Zero-Turn	Zero-Turn
Uncut Circle Radius, cm	Zero-Turn Radius	Zero-Turn Radius	Zero-Turn Radius
MOWER DECK OPTIONS			
42 Accel Deep™ (107 cm / 42 in)			
48 Accel Deep™ (122 cm / 48 in)	•	•	
48 High Capacity (122 cm / 48 in)			•
Mulching	Optional (MulchControl™)	Optional (MulchControl™)	Optional (Mulch Kit)
Cutting Height, mm (in)	25 – 102 (1 – 4), increments 6 mm (0.25)	25 – 102 (1 – 4), increments 6 mm (0.25)	25 – 102 (1 – 4), increments 6 mm (0.25)
Mower Deck Lift System	Foot Lift	Foot Lift	Foot Lift
Mower Deck Engagement	Electric	Electric	Electric
COLLECTOR			
Standard / Optional	Optional	Optional	Optional
Capacity, Itr	230	230	230
SEAT TYPE	Medium Back	High Back / ComfortGlide™	High Back / ComfortGlide™
Seat back height, cm	45.7 cm (18 in) medium-back	50.8 cm (20 in)	57.1 cm (22.5 in)
Armrest	Yes	Yes	Yes
TYRES			
Front Casters	13 × 6.5 – 6	13 × 6.5 – 6	13 × 6.5 – 6
Rear tyres	22 × 9.5 – 10	22 × 9.5 – 10	23 × 10.5 – 12
DIMENSIONS			
Height (inc. Seat), cm (in)	121 (47.6)	121 (47.6)	122.8 (48.3)
Height (inc. Seat), cm (in) – ROPS UP	178 (70.1)	178 (70.1)	179.6 (70.7)
Length, Overall, cm (in)	195.3 (76.9)	195.3 (76.9)	208 (81.9)
Width, cm (in) – incl. Mower Deck	158.7 (62.4)	158.7 (62.4)	158.7 (62.4)
Weight, approx., kg (lb)	349 (768)	351 (772)	379 (834)

 $<sup>\</sup>blacksquare$  Standard  $\square$  Optional



 $<sup>\</sup>star$  The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque could be less.

### **X900 SERIES**

	X940	X948	X949	X950R			
ENGINE							
Туре	Diesel	Diesel	Diesel	Diesel			
Rated Engine kW (hp)*, gross SAE J1995	18 (24.5) at 3,400 rpm	18 (24.5) at 3,400 rpm	18 (24.5) at 3,400 rpm	18.5 (25.2) at 3,200 rpm			
Displacement, cm³ (cu in)	903 (55.1)	903 (55.1)	903 (55.1)	1,116 (68.1)			
Cylinders	Three, cast-iron liners	Three, cast-iron liners	Three, cast-iron liners	Three, cast-iron liners			
Injection	Indirect	Indirect	Indirect	Indirect			
Fuel Tank Capacity, ltr (gal)	19.7 (5.2)	19.7 (5.2)	19.7 (5.2)	20.4 (5.4)			
VEHICLE							
Traction Drive	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic			
Drive System	Twin Touch™ Foot Pedals, 2-Wheel Drive, 2-Wheel-Steer	Twin Touch™ Foot Pedals, 4-Wheel Drive, 2-Wheel-Steer	Twin Touch™ Foot Pedals, 4-Wheel Drive, 4-Wheel-Steer	Twin Touch™ Foot Pedals, 2-Wheel Drive, 2-Wheel-Steer			
Max. Speed km/h (mph) Forward	13.7 (8.5)	13.7 (8.5)	13.7 (8.5)	14.5 (9)			
Max. Speed km/h (mph) Reverse	9.7 (6)	9.7 (6)	9.7 (6)	9.7 (6)			
Cruise Control	Standard	Standard	Standard	Standard			
Differential Lock	Standard	Standard	Standard	Standard, Hydraulic Traction Assist			
Brake System	Internal wet disc brakes; hand controled park brake; dynamic braking	Internal wet disc brakes; hand controled park brake; dynamic braking	Internal wet disc brakes; hand controled park brake; dynamic braking	Internal wet disc brakes; hand controled park brake; dynamic braking			
HYDRAULICS							
Selective Control Valves (SCVs)	2 Dual	2 Dual	2 Dual	Multifunctional Joystick			
Hydraulic Flow, I/min	21.6	21.6	21.6	20.9			
MOWER DECKS							
Available Widths / Type, cm (in)  Deck construction	122 (48) / 137 (54) / 152 (60) Forged Steel – 137/152	122 (48) / 137 (54) / 152 (60) Forged Steel – 137/152	122 (48) / 137 (54) / 152 (60) Forged Steel – 137/152	122 (48) / 137 (54) Forged Steel			
	drive over construction	drive over construction	drive over construction				
PTO Engagement	Electro-Hydraulic	Electro-Hydraulic	Electro-Hydraulic	Electric Drive Clutch			
Deck Drive	Shaft – 137/152 optional AutoConnect™	Shaft – 137/152 optional AutoConnect™	Shaft – 137/152 optional AutoConnect™	Shaft			
Deck Lift / Lower	Hydraulic	Hydraulic	Hydraulic	Hydraulic			
Height-of-Cut Range / Increment, cm (in)	2.5 – 13.3 (1 – 5.25) / 0.6 (0.25)	2.5 – 13.3 (1 – 5.25) / 0.6 (0.25)	2.5 – 13.3 (1 – 5.25) / 0.6 (0.25)	2.5 – 11.2 (1 – 4.5) / 0.6 (0.25)			
Number of Blades	3	3	3	2			
Pre-Set Height of Cut	From operator platform – standard	From operator platform – standard	From operator platform – standard	From operator platform – standard			
COLLECTOR (optional)							
Туре	3-bag-bagger	3-bag-bagger	3-bag-bagger	Optional Low or High Dump			
Capacity, ltr	500	500	500	Low Dump: 570; High Dump: 650*			
Maximum Lift Height, cm (in)	-	-	-	High Dump: 203.7 (80.2)			
Fill Indicator	-	-	-	Real-time Ultrasonic Fill Detection			
OPERATOR STATION				Till Detection			
Standard	2 piece professional comfort seat (seat back hight 53.3 cm / 21 in), suspension, optional armrest, slide rail with 14 positions (14.8 cm / 7 in)	2 piece professional comfort seat (seat back hight 53.3 cm/ 21 in), suspension, optional armrest, slide rail with 14 positions (14.8 cm/7 in)	2 piece professional comfort seat (seat back hight 53.3 cm / 21 in), suspension, optional armrest, slide rail with 14 positions (14.8 cm / 7 in)	2 piece professional comfort seat (seat back hight 53.3 cm / 21 in), suspension, optional armrest			
Optional	Standard or air suspension seat	Standard or air suspension seat	Standard or air suspension seat	Standard or air suspension seat			
DIMENSIONS							
Length, cm (in)	191 (75)	191 (75)	191 (75)	Low Dump: 338 (133) High Dump: 345 (135.8)			
Height without cab, ROPS up, cm (in) Height with cab, cm (in)	198 (78) 189 (74.3)	198 (78) 189 (74.3)	198 (78) 189 (74.3)	208 (82) 194 (76)			
Weight, kg (lb) no fuel or Mower Deck	472 (1,042)	513 (1,132)	550 (1,213)	Low Dump: 822 (1,812) High Dump: 1,014 (2,235) – incl. Hopper			
Width without Deck, cm (in)	119 (47)	119 (47)	122 (48)	118 (46)			
Ground Clearance, cm (in)	18 (7.1)	18 (7.1)	18 (7.1)	14.5 (5.7)			
Tyres Front	18 × 8.50-8	18 × 8.50-10	18 × 8.50-10	18 × 8.5-8			
Tyres Rear	26 × 12.00-12	26 × 12.00-12	26 × 12.00-12	26 × 12-12			
SAFETY	Reverse Implement Option (RIO)	Reverse Implement Option (RIO)	Reverse Implement Option (RIO)	Reverse Implement Option (RIO)			

# GET THERE FAST AND GET THINGS DONE



This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories not available in all regions. Please contact your local dealer for details. John Deere reserves the right to change specification and design of products described in this literature without notice. The green and yellow colour scheme, the leaping deer logo and the JOHN DEERE word mark are trademarks of Deere & Company.